

ProClean Paint PAINT REMOVER

Removing paint and varnish from the surface

Description

ProClean Paint penetrates between the paint and the metal, ensuring the self-removal of the paint with its highly effective formula. It is extremely simple and economical to use. It removes the paint not by melting it, but by scraping it off in the form of leaves, so the product is not contaminated and can be reused by filtration after processing. It does not damage the metal or the existing coating on the metal.

Directions For Use/Applications & Dosage Rates General Cleaning

The product should be poured into a container as needed and left in contact with the parts to be depainted for 5 to 10 minutes. This duration should be sufficient for ProClean Paint to effectively remove paint from surfaces.

For parts that cannot be placed in a container, the application method is to spray the ProClean Paint onto the painted surface. After spraying, use a brush to work the product into the surface for approximately 5 minutes to ensure it adheres properly. After this time, you should notice that the paint has been removed from the surface.

Solvent Based Cleaners

Summary

- ProClean Paint is used safely because it does not damage the metal.
- Economical and easy to use.
- Gives results in a short time and saves time.
- It can be used multiple times.

A) Organic Properties

Physical State (20°C): Liquid

Color : Colorless

Odor : Solvent Odor

B) Physical Properties

pH : 7.0-9.0 (%)

Molecular Weight : -

Explosion Limit : No

Flash Point : No

Density : 1.14-1.24 g/cm³

Solubility : Completely soluble in water.

Storage Conditions

Packaging Type : 25-30-60-200 liters original plastic drums

Storage Period : 3 years

Approvals & Certificates



Product No : SP-KS-058