

ProTank Degreaser ER-OGR

Cleaning of oil and oil residues that cause pollution on surfaces

Description

ProTank Degreaser is a solvent-based cleaner used for cleaning petroleum and oil-derived residues that accumulate and cause pollution on all kinds of metals, painted and unpainted tank surfaces, decks, engine rooms, bilge and bilge tank surfaces.

Directions For Use/Applications & Dosage Rates General Cleaning

It is recommended to use ProTank Degreaser in concentrated form for cleaning at room temperature. The amount of ProTank Degreaser to be used varies depending on the desired degree of cleanliness and the level of contamination on the surface ProTank Degreaser can be applied by methods such as brushing and soaking/immersion.

Brushing Method

Cleaning with the brushing method can be carried out on large/narrow surface areas with a small amount of deposits and dirty machine parts. Cleaning with this method also gives good results in cleaning amorphous surfaces.

Soaking/Immersion Method

Using the immersion method, disassembled equipment or machine parts are cleaned. The parts to be cleaned are submerged in a bath filled with ProTank Degreaser and left for about 30-40 minutes. The cleaning is then completed by rinsing with water.

Brushing and immersion methods can be applied together in cleaning surfaces with very heavy deposits.

Tank & Cargo Hold Cleaners

Summary

- It effectively removes carbon deposits, such as all types of oils, fuels and greases from metal and plastic surfaces.
- Penetrates quickly and deeply into the cleaned area, cleans by emulsifying oil on the oily surface.
- It can be safely applied to all metal, plastic, painted/unpainted surfaces.
- ProTank Degreaser is an easy-to-use and economical product

A) Organic Properties

Appearance

Physical State (20°C): Liquid

Color : Clear

Odor : Mild, fragrant

B) Physical Properties

pH : -

Molecular Weight : -

Explosion Limit : No

Flash Point : No

Density : 0.80-0.90 g/cm³

Solubility in Water : Completely soluble in water

Storage Conditions

Packaging Type : 25-30 liters sealed original plastic drums

Storage Period : 3 years

Approvals & Certificates



Product No : SP-KS-035