

## DESCRIPTION

**ER-OGR** is a solvent based liquid developed to clean petroleum and oil deposits over all metal, painted/unpainted tank surfaces, decks, engine rooms and bilges effectively.

Product Name	: <b><u>ER-OGR</u></b>
Document No	: SP-KS-035
Chemical Name	: Chemical Mixture
Usage Area	: Cleaning of petroleum & oil deposits accumulated on surfaces

### A. ORGANIC PROPERTIES

Appearance	
Physical Status (20°C)	: Liquid
Color	: Transparent
Odour	: Characteristic

### B. PHYSICAL PROPERTIES

pH (in conc)	: -
Molecular Weight	: -
Flash Point	: -
Density	: 0.90 – 1.00 gram / cm <sup>3</sup>
Solubility in Water	: Appreciable

## APPLICATION, FEATURES & BENEFITS

- ✓ Effectively removes all kinds of carbon deposits such as oil, grease and fat from metal or plastic surfaces.
- ✓ Penetrates quickly and thoroughly and cleans oily surfaces by emulsifying agents.
- ✓ Can be used on all types of surfaces such as painted/unpainted metals and plastics.
- ✓ Easy to apply/use and low cost.

## STORAGE INFORMATION

Packing : 25 /30 L sealed drums.

Storage Period: 3 years

## **DIRECTIONS FOR USE/APPLICATIONS & DOSAGE RATES**

It is better to use ER-OGR in its concentrated state at room temperature.

The quantity of ER-OGR to be used changes depending on the degree of contamination and cleaning desired.

ER-OGR can be applied with two different methods as brushing and soaking/immersion.

Brushing is a convenient method to clean light accumulation of large/small surface areas and contaminated engine parts. Good results can be obtained during cleaning unshaped/formless surfaces by this method.

Soaking/Immersion method can be used to clean dismantled parts or engine components efficiently. The parts to be cleaned are immersed into a bath filled with undiluted ER-OGR and waited for 30-40 minutes approximately. Then, cleaning procedure is completed by rinsing the parts with water.

Brushing and Soaking methods can be applicable together to clean highly contaminated surfaces.