

DESCRIPTION

“**ER-TEEPOL**” is water based liquid detergent. It is formulated for removing fat, oil, grease and grime. ER-TEEPOL is an environmentally friendly product and it is non-toxic, completely biodegradable and safe to be used.

Product Name	: <u>ER-TEEPOL</u>
Document No	: SP-KS-43
Chemical Name	: Chemical Mixture
Usage Area	: Petroleum and oily surfaces

A. ORGANIC PROPERTIES

Appearance	
Physical Status (20°C)	: Liquid
Color	: Ambergris
Smell	: Soft

B. PHYSICAL PROPERTIES

pH	: 11,0-12,0
Molecular Weight	: -
Flash Point	: -
Density	: 1,03-1,08 g/cm ³
Solubility in Water	: Completely

APPLICATION, FEATURES & BENEFITS

- ✓ Water based, all-purpose cleaner which can be used for wide range applications.
- ✓ Completely biodegradable
- ✓ Does not contain nonyl phenol ethoxylates or other estrogenic compounds.
- ✓ Non flammable
- ✓ Leaves no residue over surfaces.
- ✓ Promotes healthy and pleasant smell at the working area
- ✓ Cost effective.

STORAGE INFORMATION

Store at moderate temperatures

Packing: 25-30-200 L sealed plastic drum

Storage Period: 3 years.

DIRECTIONS FOR USE/APPLICATIONS & DOSAGE RATES

ER-TEEPOL is formulated as a powerful oil remover. It is water based cleaning detergent and it is used for removing oil and grease from engine rooms, decks, cabin and segments.

The product can be used for many purposes in different concentrations depending on the degree of contamination. It can be used on all surfaces where dirt, grease and oil contaminations are present. ER-TEEPOL solution can be applied by brush, mop, rags, spray-guns or tank washing systems.

In light cleanings, use 4-6% solution of ER-TEEPOL. Leave it for 5-15 minutes on the surface and then wipe away. Heat the solution to have better results. Since ER-TEEPOL is not a corrosive product, it can be used on every surface and floors.

If it is going to be used as a **Tank Cleaner** especially with the tanks carrying diesel oil, gasoline and oil; use 0.1-1% cleaning solution in fresh water and circulate, or spray with water jets. ER-TEEPOL is suitable for cleaning tank from mineral oils, edible oils and for hydrocarbon.

ER-TEEPOL is effective almost on all kinds of pollutants including fuel-oil. It is suitable for using in closed areas. It doesn't smell irritating. It will clean the surroundings and prevent from irritating odors.

If it is going to be used on **Heavy contaminated areas**, dilute ER-TEEPOL maximum 1:3 ratio. Leave the solution on the surface for 5-10 minutes then clean with brush. After the cleaning, rinse with water.